

YOMEL

SEGADORA DE DISCOS MOSCATO 2000 / 2400
MOSCATO 2000 / 2400 DISC MOWERS



El mejor trato para sus pasturas - The best treatment for your pastures

SEGADORA DE DISCOS MOSCATO 2000 / 2400 - MOSCATO 2000 / 2400 DISC MOWERS



Posición de transporte
Transport position



Segadora multidisco para enganche de 3 puntos, de corte lateral. Equipada con 5 discos de corte de 2950 RPM, el ancho de labor es de 2,10 m.

Transmisión mediante toma de fuerza para 540 RPM, cuatro correas en V y cajas de engranaje en baño de aceite.

Los discos de corte se transmiten entre sí por intermedio de engranajes rectos en baños de aceite.

La posición de transporte se realiza por medio de comandos hidráulicos desde el tractor.

Three-point hitch multidisc mowers, of lateral cut. Equipped with 5 cutting discs of 2950 RPM, of 2,10 m working width.

PTO of 540 RPM, four belts in V and gear boxes in oil baths.

The cutting discs are transmitted among themselves by means of straight gears oil baths.

Transport position is via commands from the tractor hydraulic commands.



Posición de transporte
Transport position



Equipada con 5 discos de alta velocidad de corte de 2950 RPM

Equipada con 5 discos 2950 RPM high-speed cutting

CARACTERISTICAS TECNICAS / TECHNICAL FEATURES

MODELO / MODEL	MOSCATO 2000	MOSCATO 2400
Ancho de labor / Working width	2.08 mts	2.44 mts
Cuchillas / Blades	10	12
Rotores / Rotors	5	6
Velocidad de Giro / Disc speed	2950 RPM	2950 RPM
Ancho p/transporte / Transport width	1.85 mts	1.85 mts
Altura de corte (mts) / Cutting height (m)	12 a 60 mm	12 a 60 mm
Peso aproximado / Approximate weight	415 kgs	480 kgs
Potencia de tractor recomendada Recommended power in the tractor (HP)	40 a 85 HP	40 a 85 HP
Rendimiento / Yield	1.7 a 2.2 Has/hs	2 a 2.26 Has/hs
Velocidad de Trabajo / Working speed	6 a 12 km/hs	6 a 12 km/hs
Velocidad de Transporte / Transport speed	25 km/hs	35 km/hs
Zafe Drawback	Auto por resorte a platillo Automatic by spring plate	Auto por resorte a platillo Automatic by spring plate