



## CTF14

Acoplados para tiro de camión.

Carrocería tolva metálica para transporte de fertilizantes o semillas de 14 m<sup>3</sup>

### Características:

- Peso: 1.600 Kgs.
  - **Dimensiones: 5.300 mm. de largo por 2.500 mm. de ancho.**
  - Chasis de tubo sin costura de 60 mm x 120 mm x 6,35 mm de espesor.
  - Dividida en dos cisternas.
  - Caída en los conos de 40°.
  - Descarga por medio de un tubo plegable de 240 mm. de diámetro accionado por un motor orbital de 100 cm<sup>3</sup> tipo roller.
  - Bomba de 100 Lts. con toma de fuerza de comando neumática.
  - Salidas para acoplar la manguera de otra tolva y poder descargarla.
  - Cilindro de doble acción y doble comando para manejar el sistema.
  - Depósito de 140 Lts. de aceite con filtro de salida, entrada antiespuma, boca con respirador, control de nivel y medidor de temperatura.
  - Lona tipo cobertor con manivela (Tape rápido).
  - Tratamiento Epoxi y pintura poliuretánica.
  - Accesorios incluidos: guardabarros con cortaspray, paragolpes, luces delanteras en el buche, reflectivos reglamentarios y escaleras de acceso.
  - Incluyendo colocación sobre su planta impulsora en nuestra fábrica.
- » Apta para instalar balanza.





## CTF14

Trailer for towing with a truck.

Metallic 14 m<sup>3</sup> Hopper bodywork to transport seeds or fertilizers.

### Characteristics:

- Weight: 1,600 kg.
- Size: 5,300 mm. in length by 2,500 mm. in width.
- Chassis built with seamless tubes of 60 mm by 120 mm by 6.35 mm thick.
- Divided in two tanks.
- Cones with a 40° drop.
- Unloading by means of a folding tube of 240 mm. in diameter, driven by an orbital engine of 100 cm<sup>3</sup>, roller type.
- 100 L pump. With pneumatic command power take-off
- Openings to connect hoses from other hoppers and be able to unload.
- Double acting cylinder and double command to operate the system.
- 140 L capacity oil tank with exit filters, anti-foam admission, nozzle with ventilator and oil level and temperature gauges.
- Covering tarp with crank (quick covering).
- Treated with Epoxy and polyurethane paint.
- Accessories included: mudguard with accessory to cut off spray, bumper, front statutory lights in the hold, compulsory reflecting lines and access stairs.
- Includes assembling on your propelling means at our factory.

» Scales can be fitted.

